



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/806,800	03/23/2004	Gilles G. Fayad	01CON247P-CON	2907

53375 7590 06/22/2009  
FARJAMI & FARJAMI LLP  
26522 LA ALAMEDA AVE.  
SUITE 360  
MISSION VIEJO, CA 92691

EXAMINER
----------

RIYAMI, ABDULLA A

ART UNIT	PAPER NUMBER
----------	--------------

2416

MAIL DATE	DELIVERY MODE
-----------	---------------

06/22/2009

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	<b>Application No.</b> 10/806,800	<b>Applicant(s)</b> FAYAD ET AL.	
	<b>Examiner</b> ABDULLAH RIYAMI	<b>Art Unit</b> 2416	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 22 May 2009.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 30-45, 56 and 57 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 30-45 and 56-57 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)          | 4) <input type="checkbox"/> Interview Summary (PTO-413)           |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____                                      |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)          | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____  | 6) <input type="checkbox"/> Other: _____                          |

### **DETAILED ACTION**

This is a response to an amendment/response filed on 05/22/2009.

#### ***Response to Arguments***

1. Applicant's arguments, filed 05/22/2009, with respect to the rejection(s) of claim(s) 30-45 and 56-57 under 35 U.S.C. 103(a) as being unpatentable over by Farris et al. (US 6438218 B1) in view of Walsh et al. (US 6636519 B1) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of Khanna (US 6850518).

#### ***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Art Unit: 2416

4. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

5. Claims 30-33, 38-41, and 56-57 have been rejected under 35 U.S.C. 103(a) as being unpatentable over by Farris et al. (US 6438218 B1) in view of Walsh et al. (US 6636519 B1) further in view of Khanna (US 6850518).

As per claim 30, Farris teaches of a method for use by a first gateway (see figure 4, internet module 72) to establish data communication between a first client modem (see figure 4, modem 64) and a second client modem (see figure 4, modem 66) over a packet network (see figure 4, internet 84), the method comprising: receiving a call from the first client modem over a first telephone line (see column 12, lines 23-45, internet call is made, and figure 4, internet module 72); negotiating, in response to the call, over the first telephone line with the first client modem to establish a first physical modem connection (see column 10, lines 10-67, internet module establishes connection with modem, see column 9, lines 34-40, modem establishes line connection to the internet module) between the first client modem and a first gateway of said first gateway (see column 9, lines 34-40, modem establishes line connection to the internet module);

Art Unit: 2416

informing a second gateway of the call over the packet network (see, receiver router, column 10, lines 1-30, the packets are dispatched from originator and to the destination router and internet module 74);

establishing a gateway-to-gateway transport link with the second gateway over the packet network (see TCP/IP format, column 10, lines 1-30);

determining a set of data link parameters supported by the first client modem, the first gateway, a second gateway of the second gateway and the second client modem (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations and column 6, lines 5-22, TCAP negotiations, specifying routing information);

establishing a first data link protocol over the first physical modem connection using the set of data link parameters (see column 6, lines 60-64, the lines or trunks may use digital protocols such as T1 or ISDN, each interface module also include digital service unit to generate tones, see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations);

wherein data is communicated between the first client modem and the second client modem over an end-to-end reliable connection (see TCP/IP format, column 10, lines 1-30) between the first client modem at one end and the second client modem at the other end (see figure 4, modem 64, modem 66), wherein the end-to-end reliable

Art Unit: 2416

connection (see TCP/IP format, column 10, lines 1-30) uses the set of data link parameters (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations).

Farris does not expressly disclose that the first gateway has a modem that establishes the physical connection to the client modem, and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem.

Walsh discloses that the first gateway has a modem that establishes the physical connection to the client modem (see figure 14 c, modem card and gateway card), and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames).

Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Walsh's technique of having the first gateway has a modem that establishes the physical connection to the client modem (see figure 14 c, modem card and gateway card), and the modem handshaking communications of receiving a first set

Art Unit: 2416

of data link parameters supported by said first client modem (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) as a modification in Farris's VOIP gateway method and system (see figure 4, internet module 72).

The motivation to combine would have been to have a gateway modem and client modem that is capable of detecting errors on the link in the event of any unrecoverable error that occurs affecting the communications between the modems (see column 24, lines 66-67 and column 25, lines 1-3, Walsh).

Walsh and Farris do not expressly disclose receiving a second set of data link parameters supported by both a second gateway modem of said second gateway and said second client modem, and harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem and second set of data link parameters to determine a final set of data link parameters supported by all modems.

Khanna discloses receiving a second set of data link parameters supported by both a second gateway modem of said second gateway and said second client modem (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters), and harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by

Art Unit: 2416

said first client modem and second set of data link parameters to determine a final set of data link parameters supported by all modems (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters).

Khanna, Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Khanna's technique of receiving a second set of data link parameters supported by both a second gateway modem of said second gateway and said second client modem (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters), and harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem and second set of data link parameters to determine a final set of data link parameters supported by all modems (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters) in Walsh's method and apparatus of having the first gateway has a modem that establishes the physical connection to the client modem (see figure



Art Unit: 2416

14 c, modem card and gateway card), and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) as a modification in Farris's VOIP gateway method and system (see figure 4, internet module 72).

Them motivation to combine would have been to have a method and apparatus for providing end-to-end source route information to source and destination end-stations coupled to respective local and remote route bridge sub-networks of a data link switching network (see column 1, lines 10-12, Khanna).

As per claim 56, Farris teaches of a method for use by a first gateway (see figure 4, internet module 72) to establish data communication between a first client modem (see figure 4, modem 64) and a second client modem (see figure 4, modem 66) over a packet network (see figure 4, internet 84), but does not expressly disclose harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem is performed by exchanging XID frames between said first gateway modem and said first client modem.

Walsh discloses harmonizing said set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) supported by said first gateway with said first set of data link parameters supported by said first client modem is performed by

Art Unit: 2416

exchanging XID frames between said first gateway modem and said first client modem (see figure 14b and figure 14c, modem card 408 and gateway card 605, see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605, the XID frame contains information that is used to get both cards in a link to agree on certain parameters, such as receive window size and packet bus block size, after the exchange of XID frames, it stores various agreed parameters).

Khanna, Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Walsh's technique of harmonizing said set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) supported by said first gateway with said first set of data link parameters supported by said first client modem is performed by exchanging XID frames between said first gateway modem and said first client modem (see figure 14b and figure 14c, modem card 408 and gateway card 605, see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605, the XID frame contains information that is used to get both cards in a link to agree on certain parameters, such as receive window size and packet bus block size, after the exchange of XID frames, it stores various agreed parameters) as a modification in Farris's VOIP gateway method, apparatus and system (see figure 4,

Art Unit: 2416

internet module 72) and in Khanna's end-to-end communications technique (see figure 6).

The motivation to combine would have been to have a gateway modem and client modem that is capable of detecting errors on the link in the event of any unrecoverable error that occurs affecting the communications between the modems (see column 24, lines 66-67 and column 25, lines 1-3, Walsh).

As per claim 31, Farris et al. teaches of a method, wherein the second gateway informs the second client modem of the call over a second telephone line (see, receiver router, column 10, lines 1-30, the packets are dispatched fro originator and to the destination router and internet module 74), and wherein the second gateway negotiates with the second client modem over the second telephone line to establish a second physical modem connection (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations).

As per claim 32, Walsh teaches of a method, wherein, during the harmonizing, the second gateway establishes a second data link protocol over the second physical modem connection using the set of data link parameters (see column 29, lines 5-10, call setup between client c1 and client c13, see column 29, lines 25-30, demodulates according to the modulation standard dictated by the set mode parameters transmitted to modem447, see column 29, lines 40-42, the TCP/IP protocol is employed to provide an end-to-end connection-oriented path to client c13, see also column 30, lines 5-10, an

Art Unit: 2416

outgoing call according to the modulation standard dictated by the set mode parameters transmitted over the packet bus).

Khanna, Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Walsh's technique wherein, during the harmonizing, the second gateway establishes a second data link protocol over the second physical modem connection using the set of data link parameters (see column 29, lines 5-10, call setup between client c1 and client c13, see column 29, lines 25-30, demodulates according to the modulation standard dictated by the set mode parameters transmitted to modem447, see column 29, lines 40-42, the TCP/IP protocol is employed to provide an end-to-end connection-oriented path to client c13, see also column 30, lines 5-10, an outgoing call according to the modulation standard dictated by the set mode parameters transmitted over the packet bus) as a modification in Farris's VOIP gateway method, apparatus and system (see figure 4, internet module 72) and in Khanna's end-to-end communications technique (see figure 6).

The motivation to combine would have been to have a gateway modem and client modem that is capable of detecting errors on the link in the event of any unrecoverable error that occurs affecting the communications between the modems (see column 24, lines 66-67 and column 25, lines 1-3, Walsh).

As per claim 33, Farris et al. teaches of a method, wherein the gateway-to-gateway transport link is a reliable transport link (see TCP/IP format, column 10, lines 1-

Art Unit: 2416

30). However using an unreliable transport link as the gateway-to-gateway transport link is well known in the art.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to use an unreliable transport link as the gateway-to-gateway transport link in Farris's and Walsh's telecommunication method and devices. The motivation to combine would have been to have both reliable and unreliable transport link such as TCP and UDP, so that the method can provide and charge its users, according to different types of quality of service.

As per claim 38, Farris et al. teaches of a first gateway (see figure 4, internet module 72) capable of establishing data communication between a first client modem (see figure 4, modem 64) and a second client modem (see figure 4, modem 66) over a packet network (see figure 4, internet 84), the first gateway comprising: a receiver (see figure 5, internet module) configured to receive a call from the first client modem over a first telephone line (see column 12, lines 23-45, internet call is made, and figure 4, internet module 72);

a controller (see figure 5, processor 87) configured to negotiate, in response to the call, over the first telephone line with the first client modem to establish a first physical connection (see column 10, lines 10-67, internet module establishes connection with modem, see column 9, lines 34-40, modem establishes line connection to the internet module) between the first client modem and a first gateway of said first gateway (see response to argument), wherein the controller is further configured to inform a second gateway (see, receiver router, column 10, lines 1-30, the packets are

Art Unit: 2416

dispatched from originator and to the destination router and internet module 74) of the call over the packet network and establish a gateway-to-gateway transport link (see TCP/IP format, column 10, lines 1-30) with the second gateway over the packet network (see figure 4, internet);

wherein the controller is further configured to determine a set of data link parameters supported by the first client modem, the first gateway modem, a second gateway of the second gateway and the second client modem(see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations and column 6, lines 5-22, TCAP negotiations, specifying routing information),

and establish a first data link protocol over the first physical modem connection using the set of data link parameters (see column 6, lines 60-64, the lines or trunks may use digital protocols such as T1 or ISDN, each interface module also include digital service unit to generate tones, see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations);

wherein data is communicated between the first client modem and the second client modem over an end-to-end reliable connection (see TCP/IP format, column 10, lines 1-30) between the first client modem at one end and the second client modem at the other end (see figure 4, modem 64 and modem 66, see column 6, lines 55-65, T1),

Art Unit: 2416

wherein the end-to-end reliable connection uses the set of data link parameters (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations).

Farris does not expressly disclose that the first gateway controller has a modem that establishes the physical connection to the client modem and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem.

Walsh discloses that the first gateway has a modem that establishes the physical connection to the client modem (see figure 14 c, modem card and gateway card), and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames).

Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Walsh's technique of having a first gateway controller having a modem that establishes the physical connection to the client modem (see figure 14 c, modem card and gateway card), and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem (see column 23,

Art Unit: 2416

lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) as a modification in Farris's VOIP gateway method, apparatus and system (see figure 4, internet module 72).

The motivation to combine would have been to have a gateway modem and client modem that is capable of detecting errors on the link in the event of any unrecoverable error that occurs affecting the communications between the modems (see column 24, lines 66-67 and column 25, lines 1-3, Walsh).

Walsh and Farris do not expressly disclose receiving a second set of data link parameters supported by both a second gateway modem of said second gateway and said second client modem, and the controller for harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem and second set of data link parameters to determine a final set of data link parameters supported by all modems.

Khanna discloses receiving a second set of data link parameters supported by both a second gateway modem of said second gateway and said second client modem (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters), and the controller for harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem and second set of data link parameters to



Art Unit: 2416

determine a final set of data link parameters supported by all modems (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters).

Khanna, Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Khanna's technique of receiving a second set of data link parameters supported by both a second gateway modem of said second gateway and said second client modem (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters), and harmonizing said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem and second set of data link parameters to determine a final set of data link parameters supported by all modems (see figure 6, end user A of token ring 1 with bridge 1 over IP to bridge 2 in token ring 2 for end user B, notice the exchange of XID, UA and SABME messages during setup, see column 6, lines 5-55, exchange of XID messages between end stations for reaching mutually agreeable parameters) in Walsh's method and apparatus of having the first gateway has a modem that establishes the physical connection to the client modem (see figure

Art Unit: 2416

14 c, modem card and gateway card), and the modem handshaking communications of receiving a first set of data link parameters supported by said first client modem (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) as a modification in Farris's VOIP gateway method and system (see figure 4, internet module 72).

Them motivation to combine would have been to have a method and apparatus for providing end-to-end source route information to source and destination end-stations coupled to respective local and remote route bridge sub-networks of a data link switching network (see column 1, lines 10-12, Khanna).

As per claim 39, Farris et al. teaches of a first gateway (see figure 4, block 72), wherein the second gateway informs the second client modem of the call over a second telephone line (see, receiver router, column 10, lines 1-30, the packets are dispatched fro originator and to the destination router and internet module 74), and wherein the second gateway negotiates with the second client modem over the second telephone line to establish a second physical modem connection (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translations).

As per claim 40, Walsh teaches of a controller, wherein, during the harmonizing, the second gateway establishes a second data link protocol over the second physical modem connection using the set of data link parameters (see column 29, lines 5-10, call

Art Unit: 2416

setup between client c1 and client c13, see column 29, lines 25-30, demodulates according to the modulation standard dictated by the set mode parameters transmitted to modem447, see column 29, lines 40-42, the TCP/IP protocol is employed to provide an end-to-end connection-oriented path to client c13, see also column 30, lines 5-10, an outgoing call according to the modulation standard dictated by the set mode parameters transmitted over the packet bus).

Khanna, Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Walsh's technique wherein, during the harmonizing, the second gateway establishes a second data link protocol over the second physical modem connection using the set of data link parameters (see column 29, lines 5-10, call setup between client c1 and client c13, see column 29, lines 25-30, demodulates according to the modulation standard dictated by the set mode parameters transmitted to modem447, see column 29, lines 40-42, the TCP/IP protocol is employed to provide an end-to-end connection-oriented path to client c13, see also column 30, lines 5-10, an outgoing call according to the modulation standard dictated by the set mode parameters transmitted over the packet bus) as a modification in Farris's VOIP gateway method, apparatus and system (see figure 4, internet module 72) and in Khanna's end-to-end communications technique (see figure 6).

The motivation to combine would have been to have a gateway modem and client modem that is capable of detecting errors on the link in the event of any

Art Unit: 2416

unrecoverable error that occurs affecting the communications between the modems (see column 24, lines 66-67 and column 25, lines 1-3, Walsh).

As per claim 41, Farris et al. teaches of a first gateway device, wherein the gateway-to-gateway transport link is a reliable transport link (see TCP/IP format, column 10, lines 1-30). However using an unreliable transport link as the gateway-to-gateway transport link is well known in the art.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to use an unreliable transport link as the gateway-to-gateway transport link in Farris's and Walsh's telecommunication method and devices. The motivation to combine would have been to have both reliable and unreliable transport link such as TCP and UDP, so that the method can provide and charge its users, according to different types of quality of service.

As per claim 57, Farris teaches of a first gateway (see figure 4, internet module 72) capable of establishing data communication between a first client modem (see figure 4, modem 64) and a second client modem (see figure 4, modem 66) over a packet network (see figure 4, internet 84), the first gateway comprising: a receiver (see figure 5, internet module) configured to receive a call from the first client modem over a first telephone line (see column 12, lines 23-45, internet call is made, and figure 4, internet module 72), but does not expressly disclose the controller is configured to harmonize said set of data link parameters supported by said first gateway with said first set of data link parameters supported by said first client modem is performed by exchanging XID frames between said first gateway modem and said first client modem.

Walsh discloses controller is configured to harmonize said set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) supported by said first gateway with said first set of data link parameters supported by said first client modem is performed by exchanging XID frames between said first gateway modem and said first client modem (see figure 14b and figure 14c, modem card 408 and gateway card 605, see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605, the XID frame contains information that is used to get both cards in a link to agree on certain parameters, such as receive window size and packet bus block size, after the exchange of XID frames, it stores various agreed parameters).

Khanna, Walsh and Farris are analogous art since they are from the same field of endeavor of voice calls over the packet network.

At the time of the invention, it would have been obvious to one of ordinary skill in the art to use Walsh's technique of using controller is configured to harmonize said set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605, data link layer entity that builds/parses outgoing/incoming frames, the data link layer segments data into messages or frames) supported by said first gateway with said first set of data link parameters supported by said first client modem is performed by exchanging XID frames between said first gateway modem and said first client modem (see figure 14b

Art Unit: 2416

and figure 14c, modem card 408 and gateway card 605, see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605, the XID frame contains information that is used to get both cards in a link to agree on certain parameters, such as receive window size and packet bus block size, after the exchange of XID frames, it stores various agreed parameters) as a modification in Farris's VOIP gateway method, apparatus and system (see figure 4, internet module 72) and in Khanna's end-to-end communications technique (see figure 6).

The motivation to combine would have been to have a gateway modem and client modem that is capable of detecting errors on the link in the event of any unrecoverable error that occurs affecting the communications between the modems (see column 24, lines 66-67 and column 25, lines 1-3, Walsh).

6. Claims 34 and 42 are rejected under 35 U.S.C. 103(a) as being unpatentable over Farris et al. (US 6438218 B1) in view of Walsh et al. (US 6636519 B1) further in view of Khanna (US 6850518) and further in view of Endo (US 6381038 B1).

As per claim 34, Farris and Walsh teach of a method wherein the harmonizing of the set of data link parameters (see column 12, lines 10-23 and column 6, lines 5-22, Farris, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translation) includes initiating the first data link protocol (see column 6, lines 60-64, Farris), but does not expressly disclose stalling the first data link protocol.

Art Unit: 2416

Endo et al. teaches of a method of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR(receive not ready)).

Khanna, Farris, Walsh and Endo are analogous art because they are from the same field of endeavor of modem-to-modem communications over the Internet through gateways.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to use Endo's method of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR(receive not ready)) in Farris's method of communication between a modem and gateway (see figure 4) and in Walsh's technique harmonizing set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605) by exchanging XID frames between said first gateway modem and said first client modem (see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605) and in Khanna's end-to-end communications technique (see figure 6).

The motivation to combine would have been to have a gateway in a modem-to-modem communication system, which can achieve reliable communication by reducing a possibility of communication errors.

As per claim 42, Farris and Walsh teach of a first gateway device, wherein the determining of the set of data link parameters (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translation and column 6, lines 5-22, Farris) includes initiating the first data link protocol (see column 6, lines 60-64, Farris), but does not expressly disclose stalling the first data link protocol.

Endo et al. teaches of a method of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR(receive not ready)).

Khanna, Farris, Walsh and Endo are analogous art because they are from the same field of endeavor of modem-to-modem communications over the Internet through gateways.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to use Endo's technique of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway



Art Unit: 2416

relative to signal transmission to the gateway, and a further function of detecting RNR(receive not ready)) in Farris's method of communication between a modem and gateway and in Walsh's technique harmonizing set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605) by exchanging XID frames between said first gateway modem and said first client modem (see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605) and in Khanna's end-to-end communications technique (see figure 6).

The motivation to combine would have been to have a gateway in a modem-to-modem communication system, which can achieve reliable communication by reducing a possibility of communication errors.

7. Claims 35-37 and 43-45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Farris et al. (US 6438218 B1) in view of Walsh et al. (US 6636519 B1) further in view of Khanna (US 6850518) and further in view of Endo (US 6381038 B1) and further in view of Davis et al. (US 6049902).

As per claim 35, Farris, Walsh, and Endo teach of a method of determining the set of data link parameters and the first data link protocol (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translation and column 6, lines 5-22, Farris), but does not expressly disclose the protocol being based on ITU V.42 standard.

Davis et al. (US 6049902) discloses a protocol being based on ITU V.42 standard (see column 6, lines 10-20).

Khanna, Farris, Davies, Walsh and Endo are analogous art because they are from the same field of endeavor of modem-to-modem communications over the Internet through gateways.

At the time of the invention it would have been obvious to a person of ordinary skill in the art to use Davis et al.'s ITU V.42 standard (see column 6, lines 10-20) in Farris data link protocol for reliable communications (see column 12, lines 10-23 and column 6, lines 5-22, Farris) Endo's technique of stalling the first data link protocol (see RNR, figures 12-15, and columns 25, 26, and 28) and in Walsh's technique harmonizing set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605) by exchanging XID frames between said first gateway modem and said first client modem (see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605) and in Khanna's end-to-end communications technique (see figure 6).

The motivation would have been to have a standard protocol such as the ITU V series, which describe modem operation and design in order to permit different, conforming computer systems to communicate. Thus, using a protocol such as the ITU V.42 protocol, which is an error detection and recovery via retransmission protocol, would overcome data communication errors.

As per claim 36, Endo teach of a method, wherein the stalling includes transmitting an RNR by the first gateway to the first client modem (see RNR, figures 12-

Art Unit: 2416

15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR (receive not ready)).

As per claim 37, Farris teach of a method, wherein the harmonizing of the set of data link parameters (see column 12, lines 10-23 and column 6, lines 5-22, Farris) but do not expressly disclose further including resuming the first data link protocol by transmitting an RR to the first modem

Endo discloses resuming the first data link protocol by transmitting an RR to the first modem ((see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR (receive not ready)).

Khanna, Farris, Davies, Walsh and Endo are analogous art because they are from the same field of endeavor of modem-to-modem communications over the Internet through gateways.

At the time of the invention it would have been obvious to a person of ordinary skill in the art to use Davis et al.'s ITU V.42 standard (see column 6, lines 10-20) in Farris data link protocol for reliable communications (see column 12, lines 10-23 and column 6, lines 5-22, Farris) in Endo's technique of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal

Art Unit: 2416

from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR(receive not ready)) and in Walsh's technique harmonizing set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605) by exchanging XID frames between said first gateway modem and said first client modem (see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605) and in Khanna's end-to-end communications technique (see figure 6).

The motivation would have been to have a standard protocol such as the ITU V series, which describe modem operation and design in order to permit different, conforming computer systems to communicate. Thus, using a protocol such as the ITU V.42 protocol, which is an error detection and recovery via retransmission protocol, would overcome data communication errors.

As per claim 43, Farris, Walsh, and Endo teach of a first gateway device (see column 12, lines 10-23 and column 6, lines 5-22, Farris), determining the set of data link parameters and the first data link protocol (see column 12, lines 10-23 and column 6, lines 5-22, Farris), but does not expressly disclose the protocol being based on ITU V.42 standard.

Davis et al. (US 6049902) discloses a protocol being based on ITU V.42 standard (see column 6, lines 10-20).

Khanna, Farris, Davies, Walsh and Endo are analogous art because they are from the same field of endeavor of modem-to-modem communications over the Internet through gateways.

At the time of the invention it would have been obvious to a person of ordinary skill in the art to use Davis et al.'s ITU V.42 standard (see column 6, lines 10-20) in Farris data link protocol for reliable communications (see column 12, lines 10-23 and column 6, lines 5-22, Farris) Endo's technique of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR(receive not ready)) and in Walsh's technique harmonizing set of data link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605) by exchanging XID frames between said first gateway modem and said first client modem (see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605).

The motivation would have been to have a standard protocol such as the ITU V series, which describe modem operation and design in order to permit different, conforming computer systems to communicate. Thus, using a protocol such as the ITU V.42 protocol, which is an error detection and recovery via retransmission protocol, would overcome data communication errors.

As per claim 44, Endo et al. teach of the first gateway device, wherein the stalling includes transmitting an RNR by the first gateway to the first client modem (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway

Art Unit: 2416

relative to signal transmission to the gateway, and a further function of detecting RNR (receive not ready)).

As per claim 45, Farris et al. and Endo et al. teach of the first gateway device, wherein the determining of the final set of data link parameters (see column 12, lines 10-23, communication between modem 64 and modem 66, would not be possible if link parameters are not set, the destination router and its processor perform inverse functions of the originating router and make necessary translation and column 6, lines 5-22, Farris) but do not expressly disclose further including resuming the first data link protocol by transmitting an RR to the first modem.

Endo discloses resuming the first data link protocol by transmitting an RR to the first modem (see column 28).

Khanna, Farris, Davies, Walsh and Endo are analogous art because they are from the same field of endeavor of modem-to-modem communications over the Internet through gateways

At the time of the invention it would have been obvious to a person of ordinary skill in the art to use Davis et al.'s ITU V.42 standard (see column 6, lines 10-20) in Farris data link protocol for reliable communications (see column 12, lines 10-23 and column 6, lines 5-22, Farris) Endo's technique of stalling the first data link protocol (see RNR, figures 12-15, RR and RNR signals transmission and reception, and columns 25, lines 20-25, receiving section has a function of detecting a response signal from the gateway relative to signal transmission to the gateway, and a further function of detecting RNR (receive not ready)) and in Walsh's technique harmonizing set of data

Art Unit: 2416

link parameters (see column 23, lines 32-37, data is passed between the modems on cards 403-408 and gateway card 605) by exchanging XID frames between said first gateway modem and said first client modem (see column 25, lines 20-30, while in negotiation state, each card sends an XID frame to the other card 605) and in Khanna's end-to-end communications technique (see figure 6).

The motivation would have been to have a standard protocol such as the ITU V series, which describe modem operation and design in order to permit different, conforming computer systems to communicate. Thus, using a protocol such as the ITU V.42 protocol, which is an error detection and recovery via retransmission protocol, would overcome data communication errors.

### ***Conclusion***

8. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. See form 892.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to ABDULLAH RIYAMI whose telephone number is (571)270-3119. The examiner can normally be reached on Monday through Thursday 8am-5pm EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Aung Moe can be reached on (571) 272-7314. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2416

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Aung S. Moe/  
Supervisory Patent Examiner, Art Unit 2416

/Abdullah Riyami/  
Examiner, Art Unit 2416